



CERAFLUX

An ISO 9001 Certified Company

**"The Only Indian Company Manufacturing
Wide Range of Metallurgical Products "**

CERAL CEMENT

APPLICATION :-

CERAL CEMENT is used as a binding agent. Its application is to bind together, CERAL (refractory) shape and M.S. shell.

Apply uniform layer of CERAL CEMENT up to 2mm over the surface of refractory shape which is to be joined to M.S. shell.

Air dry for 48 hours.

After air drying of CERAL CEMENT layer, gaps and openings between refractory shapes lining must be sealed by insulating material like CERAL MASTIC – 2004.

Air dry for 24 hours.

Preheat and then system is ready for use.

STANDARD PACKING: 5 kg Plastic bucket..

SHELF LIFE – Six months from the date of manufacturing in closed intact packing kept in cool and dry place.

SAFETY PRECAUTION –Store the container in cool & dry place.

NOTE:- Above information is true and accurate based on controlled laboratory testing. However user is responsible for determining suitability for application at their end. No guarantee is implied since the condition in actual use differs widely & beyond our control.

CERAFLUX INDIA PVT. LTD.

F-59, MIDC, Gokul Shirgon, Kolhapur - 416234, India.

Email : info@ceraflux.com
export@ceraflux.com

Website : www.ceraflux.com

Call : 91-231-2671008/2672175.

Fax : 91-231-2671091.

Branches All Over India

AHMEDABAD, AURANGABAD, BANGALORE, BELGAUM, CHENNAI, COIMBATORE, DELHI, FARIDABAD, PUNE, SILVASA
Exporting to Bahrain, Bangladesh, Egypt, France, Indonesia, Iran, Malaysia, Nepal, Spain, Srilanka, Thailand, UAE, USA