



CERAFLUX

An ISO 9001 Certified Company

**"The Only Indian Company Manufacturing
Wide Range of Metallurgical Products "**

CERAL MASTIC-2004V

THE PRODUCT :-

CERAL MASTIC 2004V is a alumino silicate fibrous material with excellent bonding property to MS shell and CERAL (refractory) shapes. CERAL MASTIC 2004V is of highly insulating property so reduces temperature drop to a considerable extent.

CERAL MASTIC 2004V is non wetttable to molten aluminium and of "IN SITU" hardening property.

CERAL MASTIC 2004V is very much helpful in implementing 'CLEAN METAL PRACTICE'

APPLICATION :-

Make studs of 2 to 3 mm dia. and length 6 to 8 mm on vertical walls of MS shell providing 2 to 3 inch distance between each stud.

Apply the CERAL MASTIC 2004V in moist condition on MS shell to a 15 to 20mm thickness.

Air dry for 48 hours.

Apply/fill the CERAL MASTIC 2004V wherever the minute cracks found.

Air dry for 24 hours

Shape to be torched/pre-heated with hot dross.

Smaller shapes can be oven dried.

Preheat the shape, ready for use.

STANDARD PACKING : 6 kg HDPE bucket.

SHELF LIFE – Three months from the date of manufacturing in closed intact packing kept in cool and dry place.

SAFETY PRECAUTION – Store the container in cool & dry place.

NOTE:- Above information is true and accurate based on controlled laboratory testing. However user is responsible for determining suitability for application at their end. No guarantee is implied since the condition in actual use differs widely & beyond our control.

CERAFLUX INDIA PVT. LTD.

F-59, MIDC, Gokul Shirgon, Kolhapur - 416234, India.

Email : info@ceraflux.com
export@ceraflux.com

Website : www.ceraflux.com

Call : 91-231-2671008/2672175.

Fax : 91-231-2671091.

Branches All Over India

AHMEDABAD, AURANGABAD, BANGALORE, BELGAUM, CHENNAI, COIMBATORE, DELHI, FARIDABAD, PUNE, SILVASA
Exporting to Bahrain, Bangladesh, Egypt, France, Indonesia, Iran, Malaysia, Nepal, Spain, Srilanka, Thailand, UAE, USA