



CERAFLUX

An ISO 9001 Certified Company

**"The Only Indian Company Manufacturing
Wide Range of Metallurgical Products "**

CERAL SAUCER

THE PRODUCT:

CERAL SAUCER is manufactured by using high alumina cement (asbestos free), fiber-reinforced phosphate bonded refractory material sintered at 800C.

PRODUCT FUNCTION:

CERAL SAUCER is having following advantages:

1. It is non-wetting to molten aluminium.
2. It can withstand thermal shocks from 800C to room temperature.
3. It has high strength hence life of the lining is more than conventional refractory.
4. Inclusion-free final casting.
5. Abrasion resistant.

PRECAUTIONS:

Following precautions should to be taken to get improved life of CERAL SAUCER,

1. Clean/wipe the CERAL SAUCER with a brush to remove dust/metallic particles before use.
2. Avoid using any sharp metallic tools on the CERAL SAUCER surface.
3. Clean the CERAL SAUCER and apply CERACOTE –Z after every shift.
4. Preheat the CERAL SAUCER to 200-250C/low flame burner before use.

NOTE:- Above information is true and accurate based on controlled laboratory testing. However user is responsible for determining suitability for application at their end. No guarantee is implied since the condition in actual use differs widely & beyond our control.

CERAFLUX INDIA PVT. LTD.

F-59, MIDC, Gokul Shirgon, Kolhapur - 416234, India.

Email : info@ceraflux.com
export@ceraflux.com

Website : www.ceraflux.com

Call : 91-231-2671008/2672175.

Fax : 91-231-2671091.

Branches All Over India

AHMEDABAD, AURANGABAD, BANGALORE, BELGAUM, CHENNAI, COIMBATORE, DELHI, FARIDABAD, PUNE, SILVASA
Exporting to Bahrain, Bangladesh, Egypt, France, Indonesia, Iran, Malaysia, Nepal, Spain, Srilanka, Thailand, UAE, USA