

## **CRAFTANOL - 11**

**(GRAPHITE SPIRIT BASE COATING)**

### **THE PRODUCT :**

CRAFTANOL - 11 is a Refractory Coating with Graphite as main Refractory Filler in Spirit Base Carrier.

CRAFTANOL - 11 is a ready for use (RFU) coating having excellent Suspension properties.

### **PRODUCT FUNCTION :-**

CRAFTANOL - 11 it is mainly recommended for all C.I. Casting. It can be applied by brushing / dipping/ spraying.

**APPLICATION:** - CRAFTANOL - 11 can be applied by brushing/ dipping/ spraying. For brushing CRAFTANOL - 11 is to be applied as it is after thorough mixing. Ignite the core immediately after coating.

For dipping or spraying CRAFTANOL - 11 can be used as it is or dilute to requisite consistency / viscosity by CRAFTANOL THINNER. Dilution should be 10% max by weight of coating, depending upon the type of the substrate on which coating is to be applied.

**General Note :** When relative Humidity is high >70% , proper care must be taken to dry the cores before assembling / pouring.

**PROPERTIES :** The physical property of CRAFTANOL - 11 is as follows :-

- 1) Colour : Black
- 2) Appearance : RFU Liquid
- 3) Specific Gravity : 0.98 to 1.05 @ 27 °C ± 3°C
- 4) Viscosity : 13 - 16 Sec. By B4 cup @ 27°C± 3°C
- 5) Coating by Brushing : No peel off / No cracks

**PACKING** : 30 Kg. P.C.

**SHELF LIFE** : 12 months from the date of manufacturing.