

PRODUCT DATA SHEET

CERACOTE – Z 110

(Water based Zircon coating for a Aluminium industries)

THE PRODUCT :

CERACOTE – Z 110 is a zircon rich coating from the ceracote range of foundry coatings. It is a water based coating with a remarkable stability of suspension, good covering ability with firm bonding on a substrate.

PRODUCT FUNCTION :

CERACOTE – Z 110 HAS THE FOLLOWING ADVANTAGES AS A VERSATILE FOUNDRY COATING MAINLY FOR ALUMINIUM INDUSTRIES

High content of zircon permits the use in high temperature areas. Good binding and covering property is useful for coating the ceramic/metal parts for their protection from heat / hot metal. It is useful to prevent the contamination of ferrous parts with non-ferrous melts. In aluminium industries, prevents iron pickup by melt. This coating is also good for ceramic to increase their life. For example- coating of launders, tiles, ladle shapes etc.

PROCEDURE TO APPLY THE COATING FOR CERAMIC / REFRACTORY.

Apply coating by Brushing /Spraying application to desired thickness as it is or by diluting with water (100 : 15 to 20 Product : Water)

Air Dry coating for 1 Hr. minimum

Oven dry/Torch the coating to dry, Ensure complete drying of coating before use in application.

STANDARD PACKING : 25/40 Kg. Plastic Bucket.

SHELF LIFE: - 6 Months from date of manufacturing kept in closed intact container

STORAGE: Store in cool and dry place away from direct heat.

CERAFLUX INDIA PVT. LTD.

F-59 & 60, M.I.D.C. Gokul Shirgaon, Kolhapur – 416234, Maharashtra (India)

Phone: +91 8380099227 | Email: marketing@ceraflux.com

www.ceraflux.com