

PRODUCT DATA SHEET

Product Name: CRAFTCOTE – Z 25

(Thixotropic Water Based Zircon Coating)

PRODUCT INFORMATION: CRAFTCOTE-Z-25 is a Zircon rich coating from the Craftcote range of foundry coatings. It is a water based coating with remarkable stability of suspension, good covering ability with firm bonding on substrate.

PRODUCT FUNCTION: CRAFTCOTE-Z-25 is advantage's as a versatile foundry coating, mainly for Steel, Alloy Steel, Cast Iron and non-ferrous metal industries.

APPLICATION:

- 1. Mix the product CRAFTCOTE Z-25 thoroughly and then use the material for brushing, dipping and spraying applications after dilution on No bake / cold box / shell core / oil cores.
- 2. For brushing / dipping, dilute the product by 100 : 10-20 (product : water) ratio with water. For spraying dilute the product by 100 : 20-30 (product : water) ratio with water.

After applying coating, air dry it (core / mould) for 10 to 20 minutes and then dry in oven at 150° C to 160° C for 20 minutes or by torching.

PROPERTIES: The physical properties of CRAFTCOTE – Z 25 are as follows:

Colour : Off White
Appearance : Thick Liquid

3. Specific Gravity in gm/cc. : 1.75 - 1.85 @ 27 ± 3 °C

STANDARD PACKING: 30 Kg. Bucket

SHELF LIFE: 6 Months from the date of manufacturing.

Storage: Store in cool and dry place with intact packing, keep away from direct heat.

Rev. No.: 01 Rev. Date: 17.07.2021